



Box 278, Wawanesa, Manitoba R0K 2G0 Phone: (204) 824-2666

April 23rd, 2024

RE: **Quotation #04-2024 –Material Pricing for Road Reconstruction**

GENERAL INFORMATION

The Municipality of Oakland-Wawanesa is seeking quotes for materials for rural road improvements, including:

A-Base
Pit run
Clay
Riprap (2-6")
Shale
Large diameter (36") rocks
Large diameter (24") rocks
Liquid Calcium

SCOPE OF OPERATIONS

Bids will be received for any or all materials.

MEASUREMENT AND PAYMENT

The unit price will be payment in full for materials awarded.

SPECIFICATIONS

The successful bidder will organize a time with the Public Works manager to determine an adequate job timeline.

The Contractor is required to assume responsibility for all safety requirements as per Workplace Safety and Health. Proof of current Workers Compensation Insurance is required.

ENQUIRIES

Enquiries can be directed to:
Chelsea Long
Public Works Manager
Email: pw@oakland-wawanesa.ca
Telephone: 204-901-4603

QUOTES

Quotes shall be mailed or delivered in a sealed envelope clearly marked as: "Confidential – Material Pricing for Road Improvements" and must be received by 4:30 p.m. May 15, 2024.

Mail to: Municipality of Oakland-Wawanesa
Box 278
Wawanesa, MB R0K 2G0

Hand Delivered to: Municipality of Oakland-Wawanesa
106 – Fourth Street
Wawanesa, MB.

BID SHEET

Contractor Name and Address :

All quantities are approximate

Material	Quantity	Price per yard or litre
A-Base as per Schedule "A"	1400 yards	
Pit run	500 yards	
Clay	800 yards	
Riprap (2-4")	200 yards	
Shale	500 yards	
Large Diameter (36") rock	800 yards	
Large Diameter (24") rock	800 yards	
Liquid Calcium	44,000Litres/mile	

Schedule "A"

MUNICIPALITY OF OAKLAND-WAWANESA

2024 SPECIAL A-BASE COURSE GRAVEL SPECIFICATION

PASSING SIEVE SIZE		A-BASE COURSE "A"
METRIC	IMPERIAL	
19 MM	¾"	100
16 mm	5/8"	75 - 100
4.75 mm	No. 4	40 - 70
75 um	No. 200	Min 20
MINIMUM CRUSH		40%
MAXIMUM SHALE		12%
MAXIMUM LA		45%*

(The use of fly ash as a constituent of the of the product is prohibited.)

*On testing Base Course, oversize retained on the upper sieve will be permitted to a maximum of 3% of the sample, but only if 100% of the oversize will pass a sieve having openings 3 mm larger than the upper sieve.

*For Base Course, the field tests taken during any crushing shift shall yield an average of 65% or lower passing the 4.75 mm sieve.

*Material passing the 425um sieve, must possess a liquid limit not greater than 50 and a plasticity index of not less than 10.